

ARAD OUTDOOR LIGHTING

PRIME FEATURES:

- > STAINLESS 316L
- > BEAM ANGLE OPTIONAL ON REQUEST
- > VANDAL RESISTANT SCREW
- > INDUCTION LED
- > BESPOKE FLEX AVAILABLE
- > IP67 AND IP68(24VOLTS)



APPLICATION



PART NUMBER	DESCRIPTION	POWER [W]	LUMEN	COLOUR TEMPERATURE
AL-ILL-3-WW/NW/CW	ILLUSTRO LED 3W	3W	255	3000/4000/5000K
AL-ILL-6-WW/NW/CW	ILLUSTRO LED 6W	6W	450	3000/4000/5000K
AL-ILL-9-WW/NW/CW	ILLUSTRO LED 9W	9W	810	3000/4000/5000K
AL-ILL-18-WW/NW/CW	ILLUSTRO LED 18W	18W	1530	3000/4000/5000K
ALL-ILL-30-WW/NW/CW	ILLUSTRO LED 30W	30W	2550	3000/4000/5000K



ILLUSTRO LED

WHAT YOU NEED TO KNOW:**SPECIFICATION:**

Input Voltage	110-120 VAC
INPUT FREQUENCY[HZ]	50-60
DRIVERS	INCLUDED
OPERATING TEMP C °	-40 ° TO 50 °
LIFE[H]	50,000 HOURS
IP RATING	IP67 OR IP68
BEAM ANGLE	25 °, 40 °, 60 °
WARRANTY	5 YEARS

PHYSICAL DATA:

BODY SHAPE	ROUND/SQUARE
BODY COLOUR	STAINLESS STEEL
BODY FINISH	STAINLESS STEEL
DIFFUSER COLOR	CLEAR
DIFFUSER MATERIAL	GLASS

DIMENSIONS:

DESCRIPTION	DEPTH [MM]	CUT-OUT [MM]	O/DIA [MM]
3W	75	55	70
6W	155	115	129
9W	130	185	202
18W	110	215	230
30W	110	215	230

