


### PRIME FEATURES:

- SHATTER PROOF GLASS OPTIONAL
- POLE BRACKET/ DIMMING OPTIONAL
- THERMAL SHUTDOWN PROTECTION
- IK08
- 5MM TEMPERED GLASS
- AVAILABLE IN 3000K AND 5000K



### APPLICATION



LORDINO LED

PART NUMBER	DESCRIPTION	POWER [W]	LUMEN	COLOUR TEMPERATURE
AL-LORDINO-20/30/40/50	LED LORDINO 20/30/40/50 W	20	2375	4000K
		30	3402	
		40	4476	
		50	5484	



## WHAT YOU NEED TO KNOW:

### SPECIFICATION:

Input Voltage	220-240V
INPUT FREQUENCY [HZ]	50-60
DRIVER	INCLUDED
CRI	≥80
BEAM ANGLE	110 °
LIFE[H]	50,000 HOURS
IP RATING	IP65
OPERATING TEMP° C	-25 TO 45
WARRANTY	5 YEARS

### DIMENSIONS:

DESCRIPTION	WIDTH W(MM) (A)	LENGTH L(MM) (B)	DEEP D(MM) (C)
	275	155	65

### PHYSICAL DATA:

BODY SHAPE	RECTANGULAR
BODY COLOUR	ANTHRACITE
BODY FINISH	ANTI CORROSIVE
DIFFUSER COLOUR	TRANSDAR
DIFFUSER MATERIAL	GLASS

