



Specification	
Input Voltage	110-240 AC
Input Frequency (Hz)	50-60
Drivers	INCLUDED
Beam Angle	120°
CRI	≥80
Life (H)	30000
Operating Temperature (°c)	-25 to 40
IP Rating	IP65
Warranty	3 Years

Physical Data	
Shape	RECTANGLE
Colour	BLACK
Finish	ALUMINIUM



### KEY FEATURES

- Zero UV Emission, 90 LM/W
- Upto 70% of energy savings
- 30,000 Hours life, Bridgelux Chip
- IP65, Instant light, 3000k and 4000k optional
- Photocell available
- Thermal Shutdown protection

Ordering Information						
Part Number	Power (W)	Lumen	DEPTH (mm)	Height (mm)	Width (mm)	Colour Temp
AL-FL10-SBL-BL	10	900	50	180	150	5000
AL-FL30-SBL-BL	30	2700	80	280	220	5000
AL-FL50-SBL-BL	50	4500	110	350	295	5000
AL-FL70-SBL-BL	70	6300	105	365	283	5000
AL-FL100-SBL-BL	100	9000	120	410	350	5000
AL-FL200-SBL-BL	200	18000	145	510	430	5000
AL-RGB-FL-10/50	10/50	N/A	50/110	180/350	150/295	5000

