

PRIME FEATURES:

- INSTANT LIGHT
- ZERO UV EMISSION
- BRIDGELUX CHIP
- 90 LM/W
- PHOTOCELL AVAILABLE
- 3000K AND 4000K OPTIONAL
- THERMAL SHUTDOWN PROTECTION



PRO FLOOD

APPLICATION



PART NUMBER	DESCRIPTION	POWER [W]	LUMEN	COLOUR TEMPERATURE
AL-FL10/30/50/70/100/200-SBL-BL	LED FLOOD LIGHT WITH /WITHOUT SENSOR	10/30/50 70/100/200	900/2700/ 4500/6300 9000/18000	5000K
AL-RGB-FL-10/50	RGB FLOOD LIGHT 10W/50W	10/50		5000K



PRO FLOOD

WHAT YOU NEED TO KNOW:

SPECIFICATION:

Input Voltage	110-240AC
INPUT FREQUENCY [HZ]	50-60
POWER FACTOR	>0.98
DRIVER	INCLUDED
BEAM ANGLE	60 °
CRI	≥80
LIFE[H]	50,000 HOURS
IP RATING	IP65
OPERATING TEMP° C	-25 TO 45
WARRANTY	5 YEARS

DIMENSIONS:

DESCRIPTION	WIDTH W(MM)	HEIGHT L(MM)	DEEP D(MM)
10W	150	180	50
30W	220	280	80
50W	295	350	110
70W	283	365	105
100W	350	410	120
200W	430	510	145
RGB10W	150	180	50
RGB50W	295	350	110

PHYSICAL DATA:

BODY SHAPE	RECTANGLE
BODY COLOUR	BLACK
BODY FINISH	ALUMINUM
DIFFUSER COLOUR	CLEAR
DIFFUSER MATERIAL	TOUGHENED GLASS

PHOTOMETRIC DATA

