

### PRIME FEATURES:

- STAINLESS 316L
- BEAM ANGLE OPTIONAL ON REQUEST
- VANDAL RESISTANT SCREW
- INDUCTION LED
- BESPOKE FLEX AVAILABLE
- IP67 AND IP68(24VOLTS)



### APPLICATION



PART NUMBER	DESCRIPTION	POWER [W]	LUMEN	COLOUR TEMPERATURE
AL-ILL-3-WW/NW/CW	ILLUSTRO LED 3W	3W	255	3000/4000/5000K
AL-ILL-6-WW/NW/CW	ILLUSTRO LED 6W	6W	450	3000/4000/5000K
AL-ILL-9-WW/NW/CW	ILLUSTRO LED 9W	9W	810	3000/4000/5000K
AL-ILL-18-WW/NW/CW	ILLUSTRO LED 18W	18W	1530	3000/4000/5000K
ALL-ILL-30-WW/NW/CW	ILLUSTRO LED 30W	30W	2550	3000/4000/5000K



**WHAT YOU NEED TO KNOW:**

**SPECIFICATION:**

<b>Input Voltage</b>	<b>110-120 VAC</b>
<b>INPUT FREQUENCY[HZ]</b>	<b>50-60</b>
<b>DRIVERS</b>	<b>INCLUDED</b>
<b>OPERATING TEMP C °</b>	<b>-40 ° TO 50 °</b>
<b>LIFE[H]</b>	<b>50,000 HOURS</b>
<b>IP RATING</b>	<b>IP67 OR IP68</b>
<b>BEAM ANGLE</b>	<b>25 ° , 40 ° , 60 °</b>
<b>WARRANTY</b>	<b>5 YEARS</b>

**PHYSICAL DATA:**

<b>BODY SHAPE</b>	<b>ROUND/SQUARE</b>
<b>BODY COLOUR</b>	<b>STAINLESS STEEL</b>
<b>BODY FINISH</b>	<b>STAINLESS STEEL</b>
<b>DIFFUSER COLOR</b>	<b>CLEAR</b>
<b>DIFFUSER MATERIAL</b>	<b>GLASS</b>

**DIMENSIONS:**

DESCRIPTION	DEPTH [MM]	CUT-OUT [MM]	O/DIA [MM]
3W	75	55	70
6W	155	115	129
9W	130	185	202
18W	110	215	230
30W	110	215	230

