


PRIME FEATURES:



- STAINLESS STEEL SCREW
- 50,000 HOURS LIFE
- DIE CAST BODY
- EMERGENCY/ PHOTOCELL OPTIONAL
- 80 LM/W

APPLICATION



LED WALL PACK

PART NUMBER	DESCRIPTION	POWER [W]	LUMEN	COLOUR TEMPERATURE
AL-WP-30-60-CW	WALL PACK 30W	30	2400	5000K



LED WALL PACK

WHAT YOU NEED TO KNOW:

SPECIFICATION:

Input Voltage	220-240AC
FREQUENCY	50-60
DRIVER	INCLUDED
BEAM ANGLE	120 °
CRI	≥80
LIFE[H]	50,000 HOURS
WEIGHT [KG]	2.3 KG
IP RATING	IP65
WARRANTY	5 YEARS

DIMENSIONS:

DESCRIPTION	WIDTH W(MM)	HEIGHT H(MM)	DEEP D(MM)
	264	308	182

PHYSICAL DATA:

BODY SHAPE	RECTANGULAR
BODY COLOUR	BLACK
BODY FINISH	DIE-CAST
DIFFUSER COLOUR	CLEAR
DIFFUSER MATERIAL	POLYCARBONATE

PHOTOMETRIC DATA

