

PRIME FEATURES:

- FLUSH MOUNTING BASE
- FLAT TOP
- OPTION III AND V GLASS
- IP65
- VANDAL-RESISTANT BASE AND SCREWS SCREWS



BOLLARD LED

APPLICATION



PART NUMBER	DESCRIPTION	POWER [W]	LUMEN	COLOUR TEMPERATURE
AL-BOFG3	FLAT TOP BOLLARD TYPE III GLASS	15W	1110/ 1152	4000K/ 5000K
AL-BOFG5	FLAT TOP BOLLARD TYPE V GLASS	15W	1080/ 1125	4000K/ 5000K



BOLLARD LED

WHAT YOU NEED TO KNOW:

SPECIFICATION:

Input Voltage	120-277AC
INPUT FREQUENCY[HZ]	50-60
DRIVERS	INCLUDED
CRI	≥83
OPERATING TEMP C °	-40 ° TO 40 °
LIFE[H]	50,000 HOURS
IP RATING	IP65
WARRANTY	5 YEARS

PHYSICAL DATA:

BODY SHAPE	BOLLARD
BODY COLOUR	BRONZE/WHITE/ BLACK
BODY FINISH	ALUMINUM
DIFFUSER COLOR	CLEAR
DIFFUSER MATERIAL	POLYCARBONATE

DIMENSIONS:

	D [mm]	W [mm]	H[mm]
AL-BOFG3	N/A	177.8	1041.4
AL-BOFG5	N/A	177.8	1041.4

