



Specification	
Input Voltage:	AC100~240V 50/60Hz
Power:	AL-LL24 24w AL-LL48 48w
Working Temperature:	-20~60°C
Color temperature:	2700~6500K RGB
Luminous Flux:	AL-LL24 = 1800LM AL-LL48 = 2800LM
Light Efficiency:	AL-LL24 = 75LM/W AL-LL48 = 60LM/W
CRI:	AL-LL24 = >80 AL-LL48 = >70
Control Distance:	30m
Beam Angle:	15*60°
Illumination Distance:	AL-LL24 = >15m AL-LL48 = >20m
IP Rate:	IP66
Housing Material:	Die-cast aluminium, stalinite
Product Weight:	2.36kg

KEY FEATURES

Wall wash lights. 2.4GHz RF remote controllable, WiFi enabled smart phone control. 16 Million colours to choose from, colour temperature, brightness & saturation controllable. The light housing is made of aluminium alloy with anodizing technology on the surface, and stalinite mirror surface with high light transmittance. Widely used on buildings, bridges, showcases and landscapes, etc.

Ordering Information	
Model No	Description
AL-LL24 RGB-CCT	24W WALL WASH RGB-CCT
AL-LL48 RGB-CCT	48W WALL WASH RGB-CCT

